



SIMPLY ELECTRIC EVOLVE . ELEVATE . EARN

THE EXPERT OF HIGH-FREQUENCY Z VLOGISTICS DISTRIBUTION



MORE CAPACITY

MORE SPACE

MORE RELIABILITY

MORE RANGE

SPECIFICATIONS

Basic Information	
Gross Vehicle Weight (G.V.W.)	2540 Kg.
Payload / Cargo Box Volume	1400 Kg.*
Front Axle	1.5T
Rear Axle/Reduction Ratio	2T/Ratio: 10.5
Cabin Dimensions	Width 1520 mm - Single Row
Cargobox Dimensions (mm)*	3050 X 11560 X 360-CLB / 3050 X 1560 X 1570 Container
Overall Dimensions (mm)*	4880 X 1680 X 1945
Ground Clearance	180 mm
Height of Platform	810 mm
Max Speed	90 Km/h
Range (NEDC)	280 Km*
Battery	
Battery Type	CATL Lithium Iron Phospate
Battery Capacity (kWh)	38.64 kWh
Rated Voltage (V)	309.12 V
Motor Motor	
Motor Type	Permanent Magnet Synchronous Motor
Max Power	60Kw/10000 Rpm 80HP
Peak Torque	220 N.m/10000 Rpm
Charging System	
AC Charging Power	6.6KW
AC Charging Current (A)	11:7 A
Charging Type	DC Fast Charging / AC Ślow Charging
Fast Charging/Slow charging Time(0-100)	≤1 Hour(25°c) / ≤6 Hour(25°c)
Charging Socket Type	CCS2
Brake	
Brake Type	Front Disc, Rear Drum
Brake Power Form	Vacuum Booster
ABS + EBD	√ // /
Additional Features	
Steering Type	Electric Power Steering
Air Conditioning	√
Multimedia System	1
Reverse Camera	1
Power Window 5	√ (Front)





For more information please contact:

MAW Vriddhi Commercial Vehicles Pvt. Ltd. Authorised Distributor of FOTON MOTOR GROUP Swoyambhu- 15, Kathmandu, Nepal Tel: +977 9802350841, 9802335398 Showroom: +977-01-5186375/ 5186376 Balkumari, Lalitpur www.fotonnepal.com